


RACCORDI A SALDARE ASME



FONDELLI

ASME B16.9 ASTM A 403 WP
304/304L E WP 316/316L

D.E. POLLICI	Ø EST. MM X SPESS. MM	SCH	E	PESO KG/PZ.
1/2"	21.34 x 2.11	10S	25	0.04
	21.34 x 2.77	40S		0.05
	21.34 x 3.73	80S		0.06
3/4"	26.67 x 2.11	10S	25	0.06
	26.67 x 2.87	40S		0.07
	26.67 x 3.91	80S		0.08
1"	33.40 x 2.77	10S	38	0.09
	33.40 x 3.38	40S		0.13
	33.40 x 4.55	80S		0.13
1 1/4"	42.16 x 2.77	10S	38	0.13
	42.16 x 3.56	40S		0.17
	42.16 x 4.85	80S		0.18
1 1/2"	48.26 x 2.77	10S	38	0.14
	48.26 x 3.68	40S		0.23
	48.26 x 5.08	80S		0.24
2"	60.33 x 2.77	10S	38	0.19
	60.33 x 3.91	40S		0.26
	60.33 x 5.54	80S		0.35
2 1/2"	73.03 x 3.05	10S	38	0.25
	73.03 x 5.16	40S		0.45
	73.03 x 7.01	80S		0.51

D.E. POLLICI	Ø EST. MM X SPESS. MM	SCH	E	PESO KG/PZ.
3"	88.90 x 3.05	10S	51	0.40
	88.90 x 5.49	40S		0.71
	88.90 x 7.62	80S		0.85
4"	114.30 x 3.05	10S	64	0.65
	114.30 x 6.02	40S		1.22
	114.30 x 8.56	80S		1.61
5"	141.30 x 3.40	10S	76	1.02
	141.30 x 6.55	40S		1.91
6"	168.28 x 3.40	10S	89	1.36
	168.28 x 7.11	40S		3.23
	168.28 x 10.97	80S		4.54
8"	219.08 x 3.76	10S	102	2.49
	219.08 x 8.18	40S		5.67
	219.08 x 12.70	80S		7.80
10"	273.05 x 4.19	10S	127	4.90
	273.05 x 9.27	40S		9.21
	273.05 x 12.70	80S		13.10
12"	323.85 x 4.57	10S	152	6.53
	323.85 x 9.53	40S		13.06
	323.85 x 12.70	80S		17.30

Nota: i dati tecnici su questo catalogo sono indicativi e non impegnativi