



ACCIAIO INOX



TEES UGUALI SENZA SALDATURA

ASME B16.9 ASTM A 403
WP 304/304L E WP 316/316L

D.E. POLLICI	Ø EST. MM X SPESS. MM	SCH	A	PESO KG/PZ.
1/2"	21.34 x 2.11	10S	25	0.07
	21.34 x 2.77	40S		0.08
	21.34 x 3.73	80S		0.14
	21.34 x 4.75	160		0.15
3/4"	26.67 x 2.11	10S	29	0.09
	26.67 x 2.87	40S		0.11
	26.67 x 3.91	80S		0.20
	26.67 x 5.54	160		0.30
1"	33.40 x 2.77	10S	38	0.20
	33.40 x 3.38	40S		0.24
	33.40 x 4.55	80S		0.39
	33.40 x 6.35	160		0.47
1 1/4"	42.16 x 2.77	10S	48	0.33
	42.16 x 3.56	40S		0.41
	42.16 x 4.85	80S		0.54
	42.16 x 6.35	160		0.89
1 1/2"	48.26 x 2.77	10S	57	0.46
	48.26 x 3.68	40S		0.60
	48.26 x 5.08	80S		1.02
	48.26 x 7.14	160		1.43
2"	60.33 x 2.77	10S	64	0.63
	60.33 x 3.91	40S		0.87
	60.33 x 5.54	80S		1.60
	60.33 x 8.71	160		3.18
2 1/2"	73.03 x 3.05	10S	76	1.10
	73.03 x 5.16	40S		1.70
	73.03 x 7.01	80S		3.63

D.E. POLLICI	Ø EST. MM X SPESS. MM	SCH	A	PESO KG/PZ.
3"	88.90 x 3.05	10S	86	1.37
	88.90 x 5.49	40S		1.90
	88.90 x 7.62	80S		4.45
	88.90 x 11.13	160		5.87
3 1/2"	101.6 x 3.05	10S	95	1.74
	101.6 x 5.74	40S		3.19
4"	114.30 x 3.05	10S	105	2.15
	114.30 x 6.02	40S		4.13
	114.30 x 8.56	80S		7.70
	114.30 x 13.49	160		9.76
5"	141.30 x 3.40	10S	124	3.48
	141.30 x 6.55	40S		6.55
6"	168.28 x 3.40	10S	143	4.76
	168.28 x 7.11	40S		9.73
	168.28 x 10.97	80S		13.61
8"	219.08 x 3.76	10S	178	8.46
	219.08 x 8.18	40S		18.00
	219.08 x 12.70	80S		27.40
10"	273.05 x 4.19	10S	216	14.20
	273.05 x 9.27	40S		30.60
12"	323.85 x 4.57	10S	254	21.60
	323.85 x 9.53	40S		44.30
14"	355.60 x 4.78	10S	279	48.53
	355.60 x 9.53	40S		79.38
16"	406.40 x 4.77	10S	305	58.90
	406.40 x 9.53	40S		99.70

Nota: i dati tecnici su questo catalogo sono indicativi e non impegnativi